

WOOD GAS NAILER

F 22/35 G2


Code : 12AG2235A1

■ Technical description

Code	12AG2235A1
Shooting	stroke / stroke
Dimensions	327 / 137 / 309 mm
Weight	2,48 kg
Magazine capacity	36
Length of projectiles	25 - 35 mm
Projectile diameter	2.5 mm
Maximum output per hour	500 shots/hour
Drive speed	1-2 shots/sec
Fuel	Propane/Liquid butane
Rated input	100-240 Vac, 50/60 Hz,
Battery charge time	2.0 hours
Battery capacity	2.5Ah
Battery voltage	7,2 V
Maximum setting per charge	8000 shots/charge
Operating temperature	-7°C (19°F) ~ 49°C (120°F)
Characteristic noise values in accordance with standard	EN 12549+A1

Projectiles

JDB +



JDB + yellow fuel cell
25 - 35 mm
Ø 2,5 mm



Related products



yellow fuel cell
Code : GAZ0020



Battery 7.2V 2.5Ah
Li-ion
Code : 12BAT7V



Kit charger /
adaptor
Code : 12KITCH2

More information on
our website :





A-weighted sound pressure level at the workstation	95.8 dB
A-weighted sound power level	97,8 dB
C-weighted instantaneous peak sound pressure level at the workstation	< 130 dB
Measurement uncertainty (standard)	2,5 dB
Vibration value according to EN ISO 28927-13	1.84 m/s ²
Measurement uncertainty (standard)	0.92 m/s ²
Actuation system	full sequential actuation

■ Application

Standing seam roof lugs.

■ Benefits

- Depth adjustment
- Long-life 7.2V Li-ion external battery
- Comfortable handle
- Belt hook
- Top loading of tips
- Anti-kickback system
- 5200 shots per battery charge
- Supplied in a box
- Supplied with 2 batteries and 1 charger

■ Filling the magazine

1. Pull back the spring loaded pusher until it latches into position.
- 2 Load the staples onto the top ridge of the magazine.
3. Press the button latch which is holding the pusher in place, taking care not to catch ones fingers, to release the pusher and allow it to close.

More information on our website :



All information is subject to change without notice and Alsafix cannot be held responsible for installation without prior calculation and testing.