



REBAR CUTTER PJRC160

Related products



Battery 25,2V - 5,0 Ah Li-ion Code: **PJ99946**

Charger de batterie Code: **RB90246**

Technical description

Code PJRC160

Dimensions 228 / 100 / 381 mm

Weight 7,26 Kg

25,2 V - 3 Ah Li-ion **Battery**

30 min **Charging time Operating temperature** -10 à 40°C

temperature

3.5 sec/cut for Ø16 mm **Cutting time**

> 170 cuts per charge for Ø 16 mm 290 cuts per charge for Ø 12 mm

Max. cutting diameter Ø 16 mm

Application

Designed for: cutting rebar, Plumber, heating contractor, electrician, bricklayer. General construction, precast concrete, construction ...











Benefits

- Speed: saving time and productivity
- Cleanliness of the site
- 360° rotating head
- Brushless motor for more performance
- Safety device to prevent accidental release
- Cutting of rebar up to 16 mm
- Charging time: 30 min
- Delivered in a box
- Delivered with 1 battery and 1 charger







The present technical indications are based on the knowledge and the experiments which we acquired and any error, inaccuracy, omission, editorial insufficiency which results from the technological evolution and from the research between the date of issue of this document and the acquisition date of produced cannot be set against us. The user of the product has, before his implementation, to proceed to any try allowing him to verify that the product is adapted to the envisaged use. Besides, every user of the product has to look for with the seller or with the manufacturer all the technical information inherent to the implementation in the hypothesis where the indications which he has, seem to have to be specified, whether it is for a normal or a specific use. ALSAFIX reserves the right to modify and to update the aforementioned data sheets without any advance notice. The customers are pleased to verify that they are in possession of the last edition. ALWAYS CONSULT THE SAFETY FORMS BEFORE USING A PRODUCT.







