









COILS SCREW

**ZINC PLATED
WOOD SCREW**

■ Technical description

Code	Designation			kg/ 						
full thread										
SP4025TX	4,0 x 25	2 500	225 000	378	4,0	25	19	7,8	TX20	
SP4030TX	4,0 x 30	2 500	225 000	403	4,0	30	25	7,8	TX20	
partial thread										
SP4035TX	4,0 x 35	2 500	225 000	468	4,0	35	20	7,8	TX20	
SP4040TX	4,0 x 40	2 000	180 000	427	4,0	40	25	7,8	TX20	
SP4045TX	4,0 x 45	2 000	180 000	482	4,0	45	28	8,0	TX20	
SP4050TX	4,0 x 50	1 500	135 000	402	4,0	50	30	7,8	TX20	
SP4550TX	4,5 x 50	1 125	101 250	386	4,5	50	28	8,5	TX20	
SP4555TX	4,5 x 55	1 125	101 250	415	4,5	55	36	8,8	TX20	
SP5060TX	5,0 x 60	1 125	101 250	545	5,0	60	34	9,8	TX25	
SP5070TX	5,0 x 70	750	67 500	452	5,0	70	48	9,8	TX25	
SP5080TX	5,0 x 80	750	67 500	402	5,0	80	50	9,8	TX25	
Design for VMZ standing seam of VM ZINC®										
SP5040PZ	5,0 x 40	1 500	108 000	414	5,0	40	35	9,8	PZ	

- countersunk head
- full or partial thread
- fins under the head

■ Application

Screws for wooden structures



**Wood screw -
Zinc plated**
25 - 80 mm
Ø 4,0 - 5,0 mm

Related product



Magazin screw driver
HH 80
Code : **MSC333810**

More information
on our website :



All information is subject to change without notice and Alsafix cannot be held responsible for installation without prior calculation and testing.